



Aerothatch 83 & Seeder 93

Provides relief from troublesome thatch and compaction and slit seeds all in one pass.



AEROTHATCH 83, MODELS 44830	
SWATH	48" (122 cm), 45" (114 cm) blade tip to blade tip.
SPACING	Model 44830: 3" (7.6 cm)
HITCH	Standard 3 point hitch, Category 1.
DRIVE	Std. 13/8" splined Ag. type drive shaft. PTO to gearbox, sealed bearing and sprocket, #H80 chain to blade shaft.
GEARBOX	Heavy duty 1:1 right angle reversible gearbox.
BLADES	(16) 12 ga./10 pt. (Optional: 7 ga. & 10 ga./10 pt.).
BLADE SHAFT	1.5" (38 mm) square high carbon steel.
BLADE DEPTH	0-3" (7.6 cm) in 1/4" (6.3 mm) increments.
FRAME	All welded steel construction.
ROLLER	Full width, 3.5" (8.9 cm) dia. roller with sealed bearings. Roller is integral with the skid shoes and spring loaded wiper for full width of roller.
DIMENSIONS	Height: 36" (91 cm) (with 3 pt. hitch). Length: 57" (145 cm). Width: 60" (152 cm).
SHIPPING WEIGHT	550 lbs. (250 kg)

SEEDER 93, MODEL 44835[1]	
DRIVE	Ground powered.
SEED HOPPER	100 lbs. (45.4 kg) capacity.
HOPPER AUGER	Metal cogs on a steel shaft.
SEED SHUT OFF	Remote from the operator's position.
SEED TUBES	Delivers seed to 16 discs.
FEED OPENINGS	Adjustable to the desired rate.
DIMENSIONS	Height: 33" (84 cm). Length: 13" (33 cm) Width: 56" (142 cm)
SHIPPING WEIGHT	300 lbs. (136 kg)
OPTIONAL	Drag Mat, 72-002-0021.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

[1] Must be used with 44830 Aerothatch.

