



Greensmaster® 1600 Specifications*

GREENSMaster 1600**, MODEL 04060											
ENGINE	Kawasaki®, 4-cycle, 3.7 hp (2.7 kW), air-cooled OHV engine, 3600 rpm. Displacement: 7.57 cu. in. (124 cc). Cast iron cylinder sleeve. Output shaft speed is 1800 rpm. Solid state electronic ignition with integral lighting coil. Maximum noise suppression muffler. 83 dB(A) at operator's ear.										
FUEL CAPACITY	2.64 quart (2.5 liter) capacity; regular grade unleaded gasoline.										
TRACTION DRIVE	Belt powered, split drum with differential. Two "A" section V-belts with manually activated idler pulley provide drive engagement/disengagement.										
REEL DRIVE	Positive drive belt powered reel. Manually activated jaw-type clutch provides drive engagement/disengagement.										
GROUND SPEED	Mowing speed: 1.3 mph (2.1 km/h) to 3.5 mph (5.6 km/h). Transport speed (maximum): 5.3 mph (8.5 km/h).										
DIFFERENTIAL	Peerless Series 100.										
CLUTCHES	Traction: inside belt idler. Reel: jaw type.										
BRAKE	Servicing brake; band type.										
TRACTION DRUM	Dual cast aluminum. 7.5" (19 cm) diameter.										
CONTROLS	Engine mounted: recoil starter, choke. Handle mounted: Hour meter, on/off switch, throttle lever, traction engage lever, service/part brake lever. Frame mounted: reel drive engage lever. Safety devices: neutral interlock system, servicing/park brake, enclosed drive system.										
TRANSPORT/TIRES/KICKSTAND	Two quick detachable pneumatic tires, 3.00 x 3.25-6. 15 psi (1.03 bar) tire pressure. Kickstand: loop style, 1" (2.5 cm) diameter tube. Kickstand and wheels are standard.										
REEL CONSTRUCTION	5" (12.7 cm) diameter, 8 high carbon steel blades welded to 6 stamped steel spiders.										
WIDTH OF CUT	26" (66 cm)										
HEIGHT OF CUT	.125"-1.25" (3.2 -31.8 mm)										
CLIP	.23" (5.8 mm) - 8 blade reel; .34" (8.6 mm) with Clip Kit, P/N 65-9000.										
BEDKNIFE/BEDBAR	Dual screw "click" adjustment to reel; bedknife is high carbon through-hardened steel, cutting edge hardness of 48-54 Rc. .125" (.31 cm) bedknife, standard.										
GRASS BASKET	Molded polyethylene. 2 position.										
FRONT ROLLER	Aluminum Wiehle roller standard; 2" (5.1 cm) diameter.										
DIMENSIONS	<table border="1"> <thead> <tr> <th>Overall Length</th> <th>Overall Width</th> <th>Overall Height</th> <th>Wheel Tread</th> <th>Weight</th> </tr> </thead> <tbody> <tr> <td>54.25" (138 cm)</td> <td>41" (104 cm)</td> <td>41.5" (105 cm) w/o transport tires</td> <td>37.5" (95 cm)</td> <td>230 lbs. (104 kg) w/o transport tires</td> </tr> </tbody> </table>	Overall Length	Overall Width	Overall Height	Wheel Tread	Weight	54.25" (138 cm)	41" (104 cm)	41.5" (105 cm) w/o transport tires	37.5" (95 cm)	230 lbs. (104 kg) w/o transport tires
Overall Length	Overall Width	Overall Height	Wheel Tread	Weight							
54.25" (138 cm)	41" (104 cm)	41.5" (105 cm) w/o transport tires	37.5" (95 cm)	230 lbs. (104 kg) w/o transport tires							
CERTIFICATION	Certified to meet ANSI specifications, B71.4-2004 and European Community (CE) specifications with required kits.										
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.										

** 04035 Greensmaster 1600 CARB (California Air Requirements Board)

GREENSMaster 1600 ACCESSORIES

STANDARD EQUIPMENT	
93-9039	Narrow Wiehle Roller
93-9015	Low Cut Bedknife

REEL OPTION	
112-9276	11-Blade Reel

BEDKNIFE & BEDBAR OPTIONS	
94-5885	Tournament Bedknife
104-2646	High Cut Bedknife
107-8181	Fairway Bedknife
112-9275	Microcut Bedknife
112-9278-03	Aggressive Bedbar
94-4286	High Height of Cut Bar
94-9010	Height of Cut Adjustment Bar

ROLLER & ROLLER SCRAPER OPTIONS	
95-0930	Full Roller
112-9290	Wiehle Roller Scraper
65-8560	Front Roller Extension Kit

GROOMER OPTIONS	
04132	Groomer Reel
115-1600	Groomer Brush Assembly

TRACTION UNIT ACCESSORIES	
04061	Light Kit
112-9282	Operator Presence Bail Kit
115-1886	Traction Slow Down Kit
65-9000	Clip Kit
04123	Wheel Kit
117-1441	Spark Arrestor Kit
98-8735	Jet Main Kit #62
98-8736	Jet Main Kit #60
04399	Turf Evaluator

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

The Greensmaster 1600 is manufactured in Tomah, WI ISO 9002 Certified Plant.

