



# Topdresser 1800

An 18 cubic foot, bed-mounted topdresser that is durable, flexible and delivers an even rate of application—whether light or heavy materials are required.



TOPDRESSER 1800, MODEL 44225				
<b>HOPPER CAPACITY</b>	18 cu. ft. (502 liter) or 1,476 lbs. (670 kg)			
<b>SPREADING WIDTH</b>	60" (152 cm)			
<b>TOP DRESSING SPEED</b>	Up to 8 mph (13 km/h).			
<b>TRANSPORT SPEED</b>	Up to 12 mph (19 km/h).			
<b>CONVEYOR BELT</b>	Seamless 60" (152 cm) wide belt, polyester mono-filament interwoven material w/gray PVC "v-pattern" traction surface.			
<b>METERING GATE</b>	Infinitely variable from closed to 3.5" (9 cm) opening for light to heavy applications. Flexible edge and spring release.			
<b>CONTROLS</b>	Hydraulic engage/disengage lever from operators console.			
<b>DRIVE</b>	Remote hydraulic to utility vehicle.			
<b>DIMENSIONS /WEIGHT</b>	<b>Height</b> 43" (109 cm)	<b>Length</b> 52" (132 cm)	<b>Width</b> 72.5" (184 cm)	<b>Shipping Weight</b> 893 lbs. (405 kg)
<b>WARRANTY</b>	Two-year limited warranty. refer to Operator's Manual for further details.			

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

