

## TITAN MX FEATURES



### MAXIMUM PERFORMANCE

Large 22" rear tires and 6" wide front tires give you stability and a smoother ride. The broader surface reduces impact and compaction so you get the performance you demand.



### MAXIMUM DURABILITY

The TITAN MX isn't just designed to handle acre after acre. It's designed to perform year after year, too. Commercial-grade HG-ZT3100 transmissions, heavy-duty frames with reinforced mounts and heavy-duty decks assure lasting durability.



### MAXIMUM COMFORT

A rugged mower doesn't have to mean a rugged ride. TITAN MX mowers feature a thickly padded Toro Premium seat with 3-D isolation mounts to absorb vibration.

NEW FOR 2011

# TITAN MX

There are times when **good** is just not good enough...

When **performance** means the best – bar none.

When **durable** has to be stonger...

When **comfort** has to feel better.

NOW, THERE'S  
**TITAN MX**



**3** YEAR  
LIMITED WARRANTY

**400** HOUR  
LIMITED WARRANTY

**LIFETIME**  
**FRAME**  
LIMITED WARRANTY

See owners manual for warranty details.

# TITAN®

# TITAN® MX

	ZX5020	ZX4820	ZX5420	ZX6020	MX4880	MX5480
MODEL	74840	74841	74842	74843	74871	74872
Engine*	23 hp KOHLER® Courage PRO	➔ <b>22 hp Kawasaki®</b>	➔ <b>24 hp Kawasaki</b>	➔ <b>26 hp Kawasaki</b>	22 hp Kawasaki	➔ <b>24 hp Kawasaki</b>
Engine Guard	Standard	Standard	Standard	Standard	Standard	Standard
Frame	Fully Tubular 1.5" x 3"	Fully Tubular 1.5" x 3"	Fully Tubular 1.5" x 3"	Fully Tubular 1.5" x 3"	Fully Tubular 1.5" x 3"	Fully Tubular 1.5" x 3"
Fuel Capacity	5 Gallon	5 Gallon	5 Gallon	5 Gallon	5 Gallon	5 Gallon
Deck Width	50"	➔ <b>48" 10g fabricated w/bull-nose bumper</b>	➔ <b>54" 10g fabricated w/bull-nose bumper</b>	➔ <b>60" 10g fabricated w/bull-nose bumper</b>	48" 10g fabricated w/bull-nose bumper	➔ <b>54" 10g fabricated w/bull-nose bumper</b>
Deck Depth	4"	➔ <b>4.5"</b>	4.5"	4.5"	4.5"	4.5"
Deck Mount	Standard, no-tools removal	Standard, no-tools removal	Standard, no-tools removal	➔ <b>Heavy duty, no-tools removal</b>	Heavy duty, no-tools removal	Heavy duty, no-tools removal
Deck Spindles	Standard	➔ <b>7.75" dia. / 1" Shaft</b>	7.75" dia. / 1" Shaft	7.75" dia. / 1" Shaft	7.75" dia. / 1" Shaft	7.75" dia. / 1" Shaft
Discharge Deflector	Polypropylene	➔ <b>Molded Rubber</b>	Molded Rubber	Molded Rubber	Molded Rubber	Molded Rubber
Blade-Tip Speed	18,000+ ft/min	18,000+ ft/min	18,000+ ft/min	18,000+ ft/min	18,000+ ft/min	18,000+ ft/min
Anti-Scalp Rollers	3 Standard	3 Standard + Rear Anti-scalp Skids	3 Standard + Rear Anti-scalp Skids	3 Standard + Rear Anti-scalp Skids	3 Standard + Rear Anti-scalp Skids	3 Standard + Rear Anti-scalp Skids
Foot Operated HOC	1.5" to 4.5" 13 position	1.5" to 4.5" 13 position	1.5" to 4.5" 13 position	1.5" to 4.5" 13 position	1.5" to 4.5" 13 position	1.5" to 4.5" 13 position
PTO Clutch	Mag-Stop Electric	Mag-Stop Electric	Mag-Stop Electric	Mag-Stop Electric	Mag-Stop Electric	Mag-Stop Electric
Transmissions	HG-ZT2800 w/ charge pumps	HG-ZT2800 w/ charge pumps	HG-ZT2800 w/ charge pumps	HG-ZT2800 w/ charge pumps	➔ <b>HG-ZT3100 w/ charge pumps, shock valves &amp; heavy duty gears</b>	HG-ZT3100 w/ charge pumps, shock valves & heavy duty gears
Ground Speed	7.5 mph	7.5 mph	7.5 mph	7.5 mph	7.5 mph	7.5 mph
Tires (Rear)	20" x 8"	20" x 8"	➔ <b>20" x 10"</b>	20" x 10"	➔ <b>22" x 10"</b>	22" x 10"
Tires (Front)	11" x 4" Smooth	11" x 4" Smooth	11" x 4" Smooth	11" x 4" Smooth	➔ <b>12" x 6" Smooth</b>	12" x 6" Smooth
Seat	Contoured 18" Extra-Tall	Contoured 18" Extra-Tall	Contoured 18" Extra-Tall	Contoured 18" Extra-Tall	➔ <b>Thickly-padded Toro Premium Seat</b>	Thickly-padded Toro Premium Seat
Seat Suspension	Adjustable Springs	Adjustable Springs	Adjustable Springs	Adjustable Springs	➔ <b>Full 3-D Isolation</b>	Full 3-D Isolation
Adjustable Armrests	Standard	Standard	Standard	Standard	➔ <b>Padded</b>	Padded
Steering Levers	Dual Comfort Grip™ levers w/hydraulic dampers	Dual Comfort Grip levers w/hydraulic dampers	Dual Comfort Grip levers w/hydraulic dampers	Dual Comfort Grip levers w/hydraulic dampers	➔ <b>Dual oversized Comfort Grip levers w/ hydraulic dampers</b>	Dual oversized Comfort Grip levers w/hydraulic dampers
Folding ROPS	Standard	Standard	Standard	Standard	Standard	Standard
Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard
Removable Floor Pan	Standard	Standard	Standard	Standard	Standard	Standard
Storage Dimensions: (L x W x H)	77.3" x 53.4" x 46"	77.3" x 52.4" x 46"	77.3" x 57.7" x 46"	77.3" x 63" x 46"	77.3" x 52.4" x 47"	77.3" x 57.7" x 47"
Residential & Commercial Warranty**	3-Year Limited/240 Hr	3-Year Limited/240 Hr	3-Year Limited/240 Hr	3-Year Limited/240 Hr	➔ <b>3-Year Limited / 400 Hr</b>	3-Year Limited / 400 Hr

➔ Indicates enhanced or step-up feature.

490-8232NA ©2010 The Toro Company. All rights reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. \* The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. \*\*See owners manual for warranty details.

