

| | Fixed Deck Hydro Drive | Floating Deck Hydro Drive | Fixed Deck Gear Drive | Floating Deck Gear Drive |
|---------------------------------|--|--|---|---|
| POWER SYSTEM | | | | |
| Commercial Engine | 15 hp Kawasaki® 17 hp Kawasaki | 17 hp Kawasaki KAI 19 hp Kawasaki KAI | 15 hp Kawasaki KAI | 15 hp Kawasaki KAI 17 hp Kawasaki KAI |
| Engine Starter | Recoil | Electric | Recoil | Recoil |
| Drive Tires | 16" X 6.5" – 8" (36", 40") 16" X 7.5" – 8" (48", 52") | 16" X 6.5" – 8" (36", 40") 16" X 7.5" – 8" (48", 52") | 13" X 5.0" – 6" (32") 13" X 6.5" – 6" (36", 40", 48") | 14" X 5" – 6" (32") 16" X 6.5" – 8" (36", 40", 48", 52") |
| Caster Tires | 9" X 3.5" – 4" Flat-Free Semi-Pneumatic | 9" X 3.5" – 4" Flat-Free Semi-Pneumatic | 9" X 3.5" – 4" Flat-Free Semi-Pneumatic | 9" X 3.5" – 4" Flat-Free Semi-Pneumatic ² |
| Fuel/Capacity | Gas/5 gal | Gas/5 gal | Gas/5 gal | Gas/5 gal |
| Transmission | Hydro-Gear® 10 cc pumps and Parker® motors | Hydro-Gear 10 cc pumps and Parker motors | 5-speed gearbox with 9 spline coupler | 5-speed gearbox with 9 spline coupler |
| Control System | Pistol Grips | Twin Lever | Pistol Grips or T-Bar | T-Bar |
| Hour Meter | — | Standard | — | — |
| Maximum Forward Speed | 6.2 mph | 6.2 mph | 6.2 mph | 6.2 mph; 5 mph (32") |
| Brake System | Hydraulic service brakes Manual parking brake | Hydraulic service brakes Manual parking brake | 6" band brakes | 6" band brakes; 5" band brakes (32") Manual parking brake |
| MOWING DECKS | | | | |
| Available Deck Widths | 36" 40" 48" 52" | 36" 40" 48" 52" | 32" 36" 40" 48" | 32" 36" 40" 48" 52" |
| Cutting Deck | TURBO FORCE® | TURBO FORCE | TURBO FORCE ¹ | TURBO FORCE (except 32") ² |
| Bull-nose Bumper | Standard | Standard | Standard ¹ | Standard ² |
| Adjustable Discharge Baffle | Standard | Standard | Standard (except 32") | Standard (except 32") ² |
| Rubber Discharge Chute | Standard | Standard | Standard | Standard ² |
| Spindle Housings | 9-3/8" diameter cast iron | 9-3/8" diameter cast iron | 9-3/8" diameter cast iron ¹ | 9-3/8" diameter cast iron ² |
| Spindle Bearings | Sealed ball bearings | Sealed ball bearings | Sealed ball bearings | Sealed ball bearings |
| Cutting Height | 1.0" – 4.25" | 1.0" – 4.5" quick change | 1.0" – 4.25" | 1.0" – 4.5" quick change ² |
| Blades – 36" – 40", 48", 52" | (2) 1/4" heat-treated steel (3) 1/4" heat-treated steel | (2) 1/4" heat-treated steel (3) 1/4" heat-treated steel | (2) 1/4" heat-treated steel ¹ (3) 1/4" heat-treated steel | (2) 1/4" heat-treated steel ² (3) 1/4" heat-treated steel |
| Blade Tip Speed | 18,000+ ft/min | 18,000+ ft/min | 18,000+ ft/min | 18,000+ ft/min |
| Belt Construction | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt | Aramid Fiber V-Belt |
| Anti-Scalp Rollers (32") | — | — | — | — |
| Anti-Scalp Rollers (36") | — | 2 front | — | 2 front |
| Anti-Scalp Rollers (40") | — | 3 front | — | 3 front |
| Anti-Scalp Rollers (48") | — | 3 front, optional 2 rear | — | 3 front, optional 2 rear |
| Anti-Scalp Rollers (52") | — | 4 front, 2 rear | — | 4 front, 2-rear |

| | Weight | Height | Deck Width | Deflector Width | Length |
|---|----------|--------|---------------|--------------------|--------|
| 30984 Fixed Deck, Pistol Grips – 15 hp Kaw/36" TF Deck | 532 lbs. | 44" | 37.1" | 46.6" | 80" |
| 30986 Fixed Deck, Pistol Grips – 15 hp Kaw/40" TF Deck | 547 lbs. | 44" | 41.6" | 55.5" | 75.3" |
| 30988 Fixed Deck, Pistol Grips – 17 hp Kaw/48" TF Deck | 570 lbs. | 44" | 49.6" | 63.5" | 78.3" |
| 30989 Fixed Deck, Pistol Grips – 17 hp Kaw/52" TF Deck | 593 lbs. | 44" | 53.8" | 67.6" | 79.3" |
| 30494 Floating Deck, Twin Lever – 17 hp Kaw KAI/36" TF Deck | 667 lbs. | 46" | 37.2" | 51.1" | 78.5" |
| 30496 Floating Deck, Twin Lever – 17 hp Kaw KAI/40" TF Deck | 667 lbs. | 46" | 41.6" | 55.5" | 75.3" |
| 30498 Floating Deck, Twin Lever – 19 hp Kaw KAI/48" TF Deck | 682 lbs. | 46" | 49.6" | 63.5" | 77.8" |
| 30499 Floating Deck, Twin Lever – 19 hp Kaw KAI/52" TF Deck | 721 lbs. | 46" | 53.7" | 67.6" | 77.8" |

| | Weight | Height | Deck Width | Deflector Width | Length |
|--|----------|--------|---------------|--------------------|--------|
| 30682 Fixed Deck, Pistol Grips – 15 hp Kaw KAI/32" Deck | 402 lbs. | 41" | 32.8" | 45.8" | 78" |
| 30684 Fixed Deck, Pistol Grips – 15 hp Kaw KAI/36" TF Deck | 462 lbs. | 41" | 37.1" | 46.6" | 80" |
| 30686 Fixed Deck, Pistol Grips – 15 hp Kaw KAI/40" TF Deck | 477 lbs. | 41" | 41.6" | 55.5" | 75.3" |
| 30688 Fixed Deck, Pistol Grips – 15 hp Kaw KAI/48" TF Deck | 500 lbs. | 41" | 49.6" | 63.5" | 78.3" |
| 30692 Fixed Deck, T-Bar – 15 hp Kaw KAI/32" Deck | 400 lbs. | 41" | 32.8" | 45.8" | 72" |
| 30694 Fixed Deck, T-Bar – 15 hp Kaw KAI/36" TF Deck | 460 lbs. | 41" | 37.1" | 46.6" | 74" |
| 30696 Fixed Deck, T-Bar – 15 hp Kaw KAI/40" TF Deck | 475 lbs. | 41" | 41.6" | 55.5" | 69.3" |
| 30698 Fixed Deck, T-Bar – 15 hp Kaw KAI/48" TF Deck | 498 lbs. | 41" | 49.6" | 63.5" | 72.3" |
| 30092 Floating Deck, Classic T-Bar – 15 hp Kaw KAI/32" Rec. Deck | 388 lbs. | 43.5" | 32" | 38.8" | 73" |
| 30094 Floating Deck, T-Bar – 15 hp Kaw KAI/36" TF Deck | 588 lbs. | 41" | 37.2" | 51.1" | 82.7" |
| 30096 Floating Deck, T-Bar – 15 hp Kaw KAI/40" TF Deck | 596 lbs. | 41" | 41.6" | 55.5" | 79.5" |
| 30098 Floating Deck, T-Bar – 17 hp Kaw KAI/48" TF Deck | 649 lbs. | 41" | 49.6" | 63.5" | 82" |
| 30099 Floating Deck, T-Bar – 17 hp Kaw KAI/52" TF Deck | 684 lbs. | 41" | 53.7" | 67.6" | 82" |

¹ 32" Fixed Deck (model 30682)

Type: 7/10 Fixed Deck
Deck construction: Fabricated Steel, 10-ga top, 7-ga skirt
Spindle Housings: Cast Aluminum
Blades: (2) .204" thick steel

² 32" CLASSIC Floating Deck (model 30092)

Type: Recycler Mulching
Deck construction: 12 gauge stamped steel
Spindle Housing: Cast Iron
Blade: (1) .188" thick
Belt construction: Polyester cord v-belt
Caster tires: 6.25"x3" pneumatic
Cutting height: 2" - 5"

The gross horsepower of these engines was laboratory rated by the engine manufacturer in accordance with SAE J1940.
As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.